

TVR-1608-2T

TruVision™ DVR 16, HD-TVI Hybrid 8 channel recorder, 2TB

Why the TVR 16?

The TVR 16 recorder series offers a full-featured, flexible hybrid recording solution that is ideal for (gradually) migrating an old analog video system to a modern high-resolution video system.

The TVR-1608 is a cost-effective recorder capable of recording up to 8 cameras

As a true hybrid recorder, the TVR 16 can be used with analog, HD-TVI and IP cameras.

The recorder also supports HD-CVI (up to 4 MP) and HD-AHD (up to 5 MP) cameras.

This hybrid recorder is uniquely qualified to upgrade existing analog installations, offering a competitive, feature-rich and practical solution for the market of HD analog, standard analog and hybrid recorders.

Open technology with powerful encoding

Using the open HD-TVI technology, TVR 1608 can connect to any HD-TVI camera up to 8 MP (4K) over existing coax cable.

As well as HD-TVI, TVR 16 also connects standard analog cameras and allows you to reuse existing analog cameras that do not yet need to be replaced/upgraded.

Finally, TVR 16 is capable of connecting all of its channels on IP cameras (up to 4K (8 MP)), making this is a true HD Hybrid series.

The TVR 16 can use H.264 or H.265 encoding for analog, HD-TVI and IP cameras.

HD-CVI and HD-AHD cameras are supported in H.264 encoding.

Unique intrusion integration

TVR 16 offers free integration with IP intrusion panels (Carrier) for video verification of (alarm) events. Alarm and arming/disarming events are sent from the intrusion panel to the recorder and can trigger actions in the recorder (recording, output control, PTZ control, email) and/or send notifications to TVRMobile or TruVision Navigator. The communication between recorder and panel is also monitored.

Applications

The TVR 16 is suited for upgrading small sized analog video systems in (commercial) applications (residential, small offices, small shops) where high quality video is important without expensive cable costs.



Details

- Linux embedded Plug and Play configuration
- Supports standard analog, HD-TVI, HD-AHD, HD-CVI and IP technology
- Up to 8 analog cameras or up to 8 IP cameras (when disabling all analog channels)
- Up to 8 MP (4K) HD-TVI and IP camera support
- Support for ONVIF Profile S IP cameras
- Over-the-coax control for TruVision fixed/PTZ HD-TVI cameras
- Use existing coax cabling for HD-TVI, HD-AHD and HD-CVI cameras
- Real time Full HD recording
- Supports dual stream recording on all channels
- Up to 4 TB internal storage
- Reverse video playback
- USB video export
- Start-up wizard for quick and easy installation
- HDMI, VGA and BNC video (event only) outputs
- V-stream support
- Front panel controls
- Operations through OSD/browser/software
- Integration of Aritech IP intrusion panels via SIA/XSIA reporting
- TruVision Navigator license-free client/host or standalone application
- TVRmobile app for iOS and Android
- IP Keypad support

TVR-1608-2T

TruVision™ DVR 16, HD-TVI Hybrid 8 channel recorder, 2TB

Technical specifications

General

| | |
|--------------------|----------------|
| Operating system | Embedded Linux |
| Rack mountable | Yes |
| Rack stacking size | 1 U |

Video/audio input

| | |
|---------------------------------------|--|
| Camera channels | 8 |
| Analog camera channels | 8 |
| IP camera channels | 8 (with all analog channels disabled) |
| Max. bandwidth per channel | Analog: Up to 8 Mbps (main stream)/Up to 3Mbps (sub stream) IP: follow capacity of IP camera but will not exceed 16 Mbps |
| Camera bandwidth | 128 Mbps (combined in/out) |
| Audio compression | G.711 |
| Max. analog audio In | 4-ch, RCA (2.0 Vp-p, 1 KOhm) |
| Supported video compression standards | H.264, H.265 |
| Supported video streaming standards | Onvif |

Local viewing

| | |
|-------------------------------------|------------------|
| HDMI output | 1 |
| HDMI version | 1.4 |
| VGA output | 1 |
| BNC output | 1 |
| Max. local output resolution | Full HD 1080p |
| Synchronous playback OSD (channels) | Up to 8 channels |
| Reverse playback OSD (channels) | Up to 1 channel |

Remote viewing

| | |
|--|---|
| Total available viewing bandwidth | 128 Mbps (combined in/out) |
| Max. live viewing streams | 128 |
| Max. simultaneous playback web browser | Up to 8 channels |
| Browser compatibility | Google Chrome, Internet Explorer, Mozilla Firefox, Safari |

Storage

| | |
|----------------------------------|--|
| Storage capacity | 2 TB |
| SATA interfaces | 2 |
| Maximum recording resolution | 4 K / 8 MPX (HD-TVI), 4 K / 8 MPX (IP), 4 MPX (HD-CVI), 5 MPX (HD-AHD) |
| Recording modes | Alarm, Event, Manual, Time-lapse high, Time-lapse low |
| Dual stream recording (channels) | All channels |

Networking

| | |
|-------------------------------|---|
| Network interface cards (NIC) | 1 |
| NIC type | RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface |
| DNS support | DDNS, ezDDNS, No-IP |
| HTTPS support | Yes |

External interfaces

| | |
|---------------------------|----------------|
| USB interface back | 1 |
| USB interface front | 1 |
| Serial interface | RS-232, RS-485 |
| Alarm inputs | 8 |
| Alarm outputs | 4 |
| Max. analog audio outputs | 1 |

Electrical

| | |
|-----------------------------------|--------------------------------|
| Power supply value | 12 VDC (External PSU included) |
| Power consumption without HDD (W) | Less than 20 W |

Physical

| | |
|---------------------|-------------------------------|
| Physical dimensions | 380 x 320 x 48 mm (W x D x H) |
| Colour | Black |

Environmental

| | |
|-----------------------|------------------------------------|
| Operating temperature | -10 °C to +55 °C (14 °F to 131 °F) |
| Relative humidity | 10% to 90% |

Standards & regulation

| | |
|------------|---------------------|
| Compliance | CE, REACH, RoHS, UL |
|------------|---------------------|

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 May 2021 - 14:37

